

# HEATSENSE®

C A B L E S

Specialist High-Performance Solutions

## SPECIFICATION DATA SHEET

### CABLE TYPE

PFA INSULATED EQUIPMENT WIRE

### GENERAL DESCRIPTION

SILVER AND NICKEL PLATED COPPER CONDUCTORS,  
PFA INSULATED TYPE A (SPCW) AND NA (NPCW).

### RELEVANT STANDARDS

HEATSENSE INTERNAL SPECIFICATION BASED ON BS3G 210 TYPE A & NA

Heatsense Part Number	Conductor Details				Insulation Thickness		Overall Diameter		Conductor Resistance ( $\Omega$ /km @ 20°C)		Mass	Long term current rating
	*S for SPCW *N for NPCW	Size AWG	Stranding (mm)	O/D (mm)	Area (mm <sup>2</sup> )	Min. (mm)	Nom. (mm)	Min. (mm)	Max. (mm)	SPCW (Max)	NPCW (Max)	Max. (kg/km)
HSA30*AA	30	01/0.250	0.25	0.049	0.10	0.15	0.45	0.60	377.00	387.00	0.96	2.0
HSA28*AA	28	01/0.320	0.32	0.080	0.10	0.15	0.52	0.67	229.00	234.00	1.32	3.0
HSA26*AA	26	01/0.400	0.40	0.126	0.10	0.15	0.60	0.75	146.00	148.00	1.83	4.0
HSA22*AA	22	01/0.600	0.60	0.283	0.10	0.15	0.80	0.95	64.30	65.00	3.88	7.0
HSA32*BA	32	07/0.080	0.24	0.035	0.10	0.15	0.44	0.59	558.00	605.00	0.84	1.5
HSA30*BA	30	07/0.100	0.30	0.055	0.10	0.15	0.50	0.65	353.00	377.00	1.10	2.0
HSA28*BA	28	07/0.120	0.36	0.079	0.10	0.15	0.56	0.71	244.00	258.00	1.40	3.0
HSA26*BA	26	07/0.150	0.45	0.124	0.10	0.15	0.65	0.80	159.00	166.00	1.96	4.0
HSA24*BA	24	07/0.200	0.60	0.220	0.10	0.15	0.80	0.95	88.30	91.20	3.04	6.0
HSA26*CA	26	19/0.100	0.50	0.149	0.10	0.15	0.70	0.85	130.00	139.00	2.26	5.0
HSA24*CA	24	19/0.120	0.60	0.215	0.10	0.15	0.80	0.95	89.80	94.90	2.99	6.0
HSA22*CA	22	19/0.150	0.75	0.336	0.10	0.15	0.95	1.10	58.60	61.30	4.41	8.0
HSA20*CA	20	19/0.200	1.00	0.597	0.10	0.15	1.20	1.35	32.50	33.60	7.19	11.0

\*Current ratings are based on a temperature rise of 40°C (single wire in free air)

### CABLE CHARACTERISTICS

#### VOLTAGE RATING:

300 V rms

#### TEMPERATURE RATING:

-75°C to +200°C for SILVER plated copper conductors,  
-75°C to +260°C for NICKEL plated copper conductors.

PFA is unaffected by oils, lubricants, hydraulic fluids and aircraft fuel. The material is non-flammable and is highly flexible. PFA wires are used in environments where the demands, whether thermal, electrical or mechanical, are severe. Available in 11 basic colours Black, Brown, Red, Orange, Yellow, Green, Blue, Violet, Grey, White, Pink plus natural.

**All extruded wire sizes/colours are RoHS compliant**

Information in this publication and otherwise supplied to users is based on our general experience and is given in good faith, but because of the many particular factors which are outside our knowledge which affect the use of products, no warranty is given nor is implied with respect to such information. Users should make their own enquiries to determine the suitability of products for any particular use. Freedom under patents, copyright and registered designs cannot be assumed.

This design may be subject to change without notification - please check this data sheet is still current.