

SPECIFICATION DATA SHEET

CABLE TYPE


ETFE INSULATED EQUIPMENT WIRE

GENERAL DESCRIPTION

SILVER PLATED COPPER CONDUCTOR, ETFE EXTRUDED TYPE 4 – THIN WALL INSULATION.

RELEVANT STANDARDS

GENERALLY IN ACCORDANCE WITH DEF STAN 61-12 PART 29 TYPE 4 Wires - ETFE

Conductor Details			Insulation Thickness	Overall Diameter		Conductor Resistance	Mass	 Part Number
Size AWG	Stranding (mm)	O/D (mm)	Nom. (mm)	Min. (mm)	Max. (mm)	Max. (Ω/km @ 20°C)	Max. (kg/km)	
28	7/0.120	0.36	0.17	0.65	0.75	244.00	1.37	HSE28SBY
26	19/0.100	0.50	0.17	0.79	0.89	130.00	2.25	HSE26SCY
24	19/0.120	0.60	0.17	0.89	0.99	89.70	3.00	HSE24SCY
22	19/0.150	0.75	0.17	1.04	1.14	56.60	4.35	HSE22SCY
20	19/0.200	1.00	0.17	1.29	1.39	32.50	7.10	HSE20SCY
18	19/0.250	1.25	0.18	1.56	1.70	20.70	10.85	HSE18SC3
16	19/0.300	1.50	0.18	1.81	1.95	14.30	15.02	HSE16SC3

Cables – ETFMETSHEATH (above core screened and sheathed)

ETFE Core	Diameter of Braid Strands	Diameter over Braid	Jacket Thickness	ETFMETSHEATH Cable Diameter		Cable Resistance	Mass
Size AWG	Nom. (mm)	Nom. (mm)	Min. (mm)	Min. (mm)	Max. (mm)	Max. (Ω/km @ 20°C)	Max. (Kg/Km)
26	0.100	1.29	0.15	1.54	1.74	135.00	8.67
24	0.100	1.39	0.15	1.64	1.84	93.30	9.65
22	0.100	1.54	0.15	1.79	1.99	61.00	11.37
20	0.100	1.79	0.15	2.04	2.24	33.80	15.35
18	0.100	2.06	0.15	2.31	2.65	21.50	21.36
16	0.100	2.31	0.15	2.56	2.90	14.80	26.79

CABLE CHARACTERISTICS

VOLTAGE RATING:

600 V rms Maximum

TEMPERATURE RATING:

-40°C (flexed) or -75°C (fixed) to +150°C

ETFE is very tough/strong, has excellent chemical resistance, radiation resistant, light weight, flame resistant, high flex life, good outgassing characteristics, and is easy to strip/handle and install.

Available in 11 basic colours Black, Brown, Red, Orange, Yellow, Green, Blue, Violet, Grey, White, Pink (plus natural) along with bi- colour combinations.

Information in this publication and otherwise supplied to users is based on our general experience and is given in good faith, but because of the many particular factors which are outside our knowledge which affect the use of products, no warranty is given nor is implied with respect to such information. Users should make their own enquiries to determine the suitability of products for any particular use. Freedom under patents, copyright and registered designs cannot be assumed.

This design may be subject to change without notification - please check this data sheet is still current.