

HEATSENSE®

C A B L E S

Specialist High-Performance Solutions

HEATSENSE SPECIFICATION DATA SHEET

CABLE TYPE

FEP INSULATED EQUIPMENT WIRE TYPE "KK"

GENERAL DESCRIPTION

SILVER OR TIN PLATED COPPER CONDUCTORS,
FEP INSULATED, EXTRUDED.

RELEVANT STANDARDS

MANUFACTURED AND TESTED IN ACCORDANCE
WITH MIL-W-16878/12 (S.P.C.W.) AND NEMA HP-4.

Part Number	Conductor Details				Overall Diameter		Conductor Resistance (Ω /km @ 20°C)		Mass (g/m)	
	#= S=SPCW T=TPCW	Size AWG	Stranding (mm)	Stranding (AWG)	Diameter Nominal (mm)	Min. (mm)	Max. (mm)	SPCW (Max.)		TPCW (Max.)
HSF32#B9		32	07/0.079	7 x 40	0.236	0.91	1.11	558	597	1.92
HSF30#B9		30	07/0.102	7 x 38	0.305	0.97	1.17	328	354	2.31
HSF28#B9		28	07/0.127	7 x 36	0.381	1.04	1.24	209	224	2.81
HSF26#B9		26	07/0.160	7 x 34	0.480	1.14	1.35	130	140	3.57
HSF26#C9		26	19/0.102	19 x 38	0.478	1.14	1.35	122	131	3.69
HSF24#B9		24	07/0.203	7 x 32	0.610	1.27	1.47	80.4	86.0	4.64
HSF24#C9		24	19/0.127	19 x 36	0.600	1.27	1.47	77.4	83.3	4.73
HSF22#B9		22	07/0.254	7 x 30	0.762	1.42	1.63	51.2	54.8	6.22
HSF22#C9		22	19/0.160	19 x 34	0.752	1.42	1.63	48.6	52.2	6.43
HSF20#B9		20	07/0.320	7 x 28	0.960	1.63	1.83	32.2	34.1	8.69
HSF20#C9		20	19/0.203	19 x 32	0.955	1.63	1.83	29.8	32.0	9.08
HSF18#C9		18	19/0.254	19 x 30	1.194	1.88	2.13	21.4	20.4	12.9
HSF16#C9		16	19/0.287	19 x 29	1.349	2.11	2.41	13.5	15.8	16.5
HSF14#C9		14	19/0.361	19 x 27	1.81	2.46	2.86	9.42	10.0	24.4
HSF12#C9		12	19/0.454	19 x 25	2.27	2.91	3.31	5.94	6.30	36.9
HSF10#D9		10	37/0.404	37 x 26	2.743	3.48	3.89	3.90	4.13	50.5
HSF08#39		8	133/0.287	133 x 29	4.089	5.05	5.56	2.17	2.30	94.4
HSF06#39		6	133/0.361	133 x 27	5.210	7.26	7.64	1.37	1.46	173.0

CABLE CHARACTERISTICS

VOLTAGE RATING:

1000 V rms

TEMPERATURE RATING:

-65°C TO +150°C FOR TPCW (As Per NEMA Spec.)

-65°C TO +200°C FOR SPCW (As Per NEMA/MIL Spec.)

Available in 10 basic colours Black, Brown, Red, Orange, Yellow, Green, Blue, Violet, Grey, White (plus natural and pink) along with bi-colour combinations.

All extruded wire sizes/colours are RoHS compliant

Information in this publication and otherwise supplied to users is based on our general experience and is given in good faith, but because of the many particular factors which are outside our knowledge which affect the use of products, no warranty is given nor is implied with respect to such information. Users should make their own enquiries to determine the suitability of products for any particular use. Freedom under patents, copyright and registered designs cannot be assumed.

This design may be subject to change without notification - please check this data sheet is still current.

ORIGINATOR: A. RABY

ISSUE: 1

06/11/2020