

JA7210 Technical Data Sheet

| | |
|---------------------------------------|--|
| Part Number | JA7210 |
| Conductor Material | Type J - Iron/Constantan |
| Construction | Each Core PFA Insulated Then Twisted Together |
| Insulation | PFA |
| Colour Code | To IEC 584-3 Black and White |
| Number of cores | 2 |
| Number of strands | 7 |
| Conductor size (mm) | 0.2 |
| Cross section area (mm ²) | 0.22 |
| Nominal overall diameter (mm) | 1.8 Nominal |
| Insulation temperature rating (°C) | -75 to + 260°C |
| Voltage rating | 240 Volts RMS |
| Current rating | N/A |
| Conductor resistance (Ohms/km @ 20°C) | |
| Specification | EMF To BSEN60584-1 1996 (Type JX) Tolerances To BSEN60584-2 1993 Class 1 @ 0° C to 300° C |

Please note there is a tolerance of +/- 10 % on cable lengths

Cable may be supplied in varying lengths. If you have specific length requirements please let us know.
All information contained within this document is believed to be reliable but cannot be guaranteed. The user shall determine the suitability of the product for its particular purpose.

Registered office: Harborough Innovation Centre, Airfield Business Park, Leicester Road, Market Harborough,
Leicestershire, LE16 7WB

Registered in England & Wales with company number: 08719200
VAT Registration number: GB 191 3285 05