

## MKP 729 Technical Data Sheet

|                                       |  |
|---------------------------------------|--|
| Part Number                           | MKP 729  |
| Conductor Material                    | Type K Nickel Chromium /Nickel Aluminium   |
| Construction                          | Each Core HRPVC Insulated Laid Flat with an Overall HRPVC Sheath                           |
| Insulation                            | PVC  |
| Colour Code                           | To IEC 584-3 Colour Code Green and White Overall Green                                     |
| Number of cores                       | 2  |
| Number of strands                     | 7  |
| Conductor size (mm)                   | 0.2  |
| Cross section area (mm <sup>2</sup> ) | 0.22   |
| Nominal overall diameter (mm)         | 2.9 x 4.5 Nominal  |
| Insulation temperature rating (°C)    | -75 to + 105   |
| Voltage rating                        | 240 Volts RMS  |
| Current rating                        | N/A  |
| Conductor resistance (Ohms/km @ 20°C) |  |
| Specification                         | EMF To BSEN60584-1 1996 (Type KX) Tolerances<br>To BSEN60584-2 1993 Class 2 @ 0°C to 100°C |

Please note there is a tolerance of +/- 10 % on cable lengths  
Cable may be supplied in varying lengths. If you have specific length requirements please let us know.  
All information contained within this document is believed to be reliable but cannot be guaranteed. The user shall determine the suitability of the product for its particular purpose.