

TA7210 Technical Data Sheet

Part Number	TA7210
Conductor Material	Type T Copper / Constantan
Construction	Each Core PFA Insulated Laid Flat Overall PFA Sheath
Insulation	PFA
Colour Code	IEC584-3 Brown and White Cores Overall Brown
Number of cores	2
Number of strands	7
Conductor size (mm)	0.2
Cross section area (mm ²)	0.22
Nominal overall diameter (mm)	1.25 x 2.3 Nominal
Insulation temperature rating (°C)	-75 to + 260
Voltage rating	240
Current rating	N/A
Conductor resistance (Ohms/km @ 20°C)	
Specification	EMF To BSEN60584-1 1996 (Type TX) Tolerances To BSEN60584-2 1993 Class 1 @ 0°C to 300°C

Please note there is a tolerance of +/-10 % on cable lengths

Cable may be supplied in varying lengths. If you have specific length requirements please let us know.
All information contained within this document is believed to be reliable but cannot be guaranteed. The user shall determine the suitability of the product for its particular purpose.

Registered office: Harborough Innovation Centre, Airfield Business Park, Leicester Road, Market Harborough,
Leicestershire, LE16 7WB

Registered in England & Wales with company number: 08719200
VAT Registration number: GB 191 3285 05