

TA7258 Technical Data Sheet

| Part Number | TA7258 |
|---------------------------------------|---|
| Conductor Material | Type T Copper / Constantan |
| Construction | Each Core PFA Insulated Twisted into 10 Pairs Each Pair Twisted Together Plus a Tinned Plated Copper Screen With an Overall PFA Jacket |
| Insulation | PFA |
| Colour Code | Constantan Legs White Copper Legs Brown Red Orange Yellow Green Blue Violet Grey Pink and Black |
| Number of cores | 20 |
| Number of strands | 7 Per Core |
| Conductor size (mm) | 0.2 |
| Cross section area (mm²) | 0.22 |
| Nominal overall diameter (mm) | 2.8 Nominal |
| Insulation temperature rating (°C) | -75 to + 260 |
| Voltage rating | 240 |
| Current rating | N/A |
| Conductor resistance (Ohms/km @ 20°C) | |
| Specification | EMF To BSEN60584-1 1996 (Type TX) Tolerances To BSEN60584-2 1993 Class 1 @ 0°C to 300°C |

Please note there is a tolerance of +/ -10 % on cable lengths

Cable may be supplied in varying lengths. If you have specific length requirements please let us know.

All information contained within this document is believed to be reliable but cannot be guaranteed. The user shall determine the suitability of the product for its particular purpose.