

# HEATSENSE®

C A B L E S

Specialist High-Performance Solutions

## HEATSENSE SPECIFICATION DATA SHEET

**CABLE TYPE**


FEP INSULATED / SHEATHED THERMOCOUPLE CABLES


**GENERAL DESCRIPTION**


THERMOCOUPLE, EXTENSION AND COMPENSATING CABLES FOR USE OVER WIDE TEMPERATURE RANGE AS A FLEXIBLE, COMPARATIVELY LOW DIAMETER CABLE IN AUTOCLAVE, LABORATORY, STERILISER APPLIANCES AND ELECTRICAL EQUIPMENT APPLICATIONS, UTILIZING VARIOUS CONSTRUCTIONS.


**RELEVANT STANDARDS**

IEC 60584/2, ANSI MC96.1, ASTM E230 THERMOCOUPLE  
IEC 60584/3, ANSI MC96.1, ASTM E230 EXTENSION/COMPENSATING

TWISTED PAIR -75°C to +200°C										
Construction	Conductor Size	Approximate Equivalent AWG	Core Diameter	Cable Diameter	Available Standards*					Part Number
					K	T	J	N	E	
	01/0.200mm	32	0.50	1.00	✓	✓	✓	✓	✓	
	01/0.300mm	28	0.60	1.20	✓	✓	✓	✓	✓	
	01/0.500mm	24	0.80	1.60	✓	✓	✓	✓	✓	
	07/0.200mm	24	0.90	1.80	✓	✓	✓	✓	✓	
	13/0.200mm	22	1.13	2.26	✓	✓	✓	✓	✓	

TWISTED PAIR, SHEATHED -75°C to +200°C										
Construction	Conductor Size	Approximate Equivalent AWG	Core Diameter	Cable Diameter	Available Standards*					Part Number
					K	T	J	N	E	
	01/0.200mm	32	0.50	1.40	✓	✓	✓	✓	✓	
	01/0.300mm	28	0.60	1.60	✓	✓	✓	✓	✓	
	01/0.500mm	24	0.80	2.00	✓	✓	✓	✓	✓	
	07/0.200mm	24	0.90	2.20	✓	✓	✓	✓	✓	
	13/0.200mm	22	1.13	2.66	✓	✓	✓	✓	✓	

TWISTED PAIR, SCREENED AND SHEATHED -75°C to +200°C										
Construction	Conductor Size	Approximate Equivalent AWG	Core Diameter	Cable Diameter	Available Standards*					Part Number
					K	T	J	N	E	
	01/0.200mm	32	0.50	1.85	✓	✓	✓	✓	✓	
	01/0.300mm	28	0.60	2.05	✓	✓	✓	✓	✓	
	01/0.500mm	24	0.80	2.45	✓	✓	✓	✓	✓	
	07/0.200mm	24	0.90	2.75	✓	✓	✓	✓	✓	
	13/0.200mm	22	1.13	3.21	✓	✓	✓	✓	✓	

FLAT TWIN -75°C to +200°C										
Construction	Conductor Size	Approximate Equivalent AWG	Core Diameter	Cable Diameter	Available Standards*					Part Number
					K	T	J	N	E	
	01/0.200mm	32	0.50	1.40 x 0.90	✓	✓	✓	✓	✓	
	01/0.300mm	28	0.60	1.60 x 1.00	✓	✓	✓	✓	✓	
	01/0.500mm	24	0.80	2.00 x 1.20	✓	✓	✓	✓	✓	
	07/0.200mm	24	0.90	2.20 x 1.30	✓	✓	✓	✓	✓	
	13/0.200mm	22	1.13	2.66 x 1.53	✓	✓	✓	✓	✓	

\*Above are just a standard selection of TH, EX & CO cables. Heatsense can offer all thermocouple types in any country code colours, please contact our sales office for any requirement.

Information in this publication and otherwise supplied to users is based on our general experience and is given in good faith, but because of the many particular factors which are outside our knowledge which affect the use of products, no warranty is given nor is implied with respect to such information. Users should make their own enquiries to determine the suitability of products for any particular use. Freedom under patents, copyright and registered designs cannot be assumed. This design may be subject to change without notification - please check this data sheet is still current.