

Specialist High-Performance Solutions

## **HEATSENSE SPECIFICATION DATA SHEET**

CABLE TYPE FEP INSULATED AWM EQUIPMENT WIRE

GENERAL DESCRIPTION TIN PLATED COPPER CONDUCTORS,

FEP EXTRUDED 0.35mm NOMINAL R/T.

RELEVANT STANDARDS UL STYLE 1333

Heatsense	Conductor Details				Insulation Thickness		Overall Diameter		Conductor	Mass	Long term
Part									Resistance		current
Number					(mm)				$(\Omega/\text{km } @ 20^{\circ}\text{C})$		rating
	Size	Stranding	O/D	Area	Min.	Min.	Min.	Nom.	TPCW	Nom.	Max.
	AWG	(mm)	(mm)	(mm²)	Ave.	AAP	(mm)	(mm)	(Max)	(kg/km)	*(A)
HSF30TBV.	30	07/0.100	0.30	0.055	0.33	0.31	0.96	1.00	353.00	3.56	2.0
HSF28TBV.	28	07/0.127	0.38	0.089	0.33	0.31	1.04	1.08	217.00	4.01	3.0
HSF26TBV.	26	07/0.160	0.48	0.141	0.33	0.31	1.14	1.18	139.00	4.76	4.0
HSF24TBV.	24	07/0.200	0.60	0.220	0.33	0.31	1.26	1.30	87.20	6.22	6.0
HSF22TCV.	22	19/0.160	0.80	0.336	0.33	0.31	1.46	1.50	51.40	7.80	8.0
HSF20TCV.	20	19/0.200	1.00	0.597	0.33	0.31	1.66	1.70	32.30	11.14	11.0
HSF18TCV.	18	19/0.250	1.25	0.933	0.33	0.31	1.91	1.95	20.30	15.17	15.0
HSF16TCV.	16	19/0.300	1.50	1.340	0.33	0.31	2.16	2.20	14.00	18.62	18.0
HSF14TCV.	14	19/0.361	1.81	1.946	0.33	0.31	2.47	2.51	9.50	26.60	25.0
HSF12TCV.	12	19/0.450	2.25	3.020	0.33	0.31	2.91	2.95	6.28	38.20	35.0
HSF10TDV.	10	37/0.400	2.80	4.650	0.33	0.31	3.46	3.50	4.02	54.90	47.0
*Current ratings are based on a temperature rise of 40°C (single wire in free air)											

Available in 11 basic colours Black, Brown, Red, Orange, Yellow, Green, Blue, Violet, Grey, White, Pink plus natural. Available in alternative conductor sizes – check for availability.

## **CABLE CHARACTERISTICS**

VOLTAGE RATING: 300 V rms

TEMPERATURE RATING: +150°C

USE: Internal wiring of appliances and electronic equipment.

600 Volts peak - For Electronic Use Only.

Suitable for immersion in gasoline; gasoline vapour; and 80°C in oil.

Information in this publication and otherwise supplied to users is based on our general experience and is given in good faith, but because of the many particular factors which are outside our knowledge which affect the use of products, no warranty is given nor is implied with respect to such information. Users should make their own enquiries to determine the suitability of products for any particular use. Freedom under patents, copyright and registered designs cannot be assumed.

This design may be subject to change without notification - please check this data sheet is still current.

CREATED BY: A. RABY ISSUE 2 24/09/2020